



- Cordless operation
- Wand tilt
- Smooth or embossed slat finish
- Snow White color
- 3" Crown valance included

Specifications:

1. HEADRAIL	1.5" High x 2" Wide low profile PVC
2. BOTTOMRAIL	Rectangular, hollow PVC bottomrail with end caps
3. SLATS	2" Wide Faux Wood PVC
4. VALANCE	3" crown profile valance. Flush installation or returns provided. Clips are concealed behind valance.
5. WAND TILTER	The tilt wand is electro zinc coated solid steel measuring 1/4 inch at its widest points. The tilter wheel is made of acetal thermoplastic and the gear and housing are made of steel to provide smooth, quiet operation.
6. CORDLESS	Cordless design with a simple raise and lower by grasping the bottomrail. Incorporates a "crash proof" safety feature that locks blind automatically upon release of bottomrail.
7. CORD LADDER	Polyester braided cord ladders provide maximum strength and flexibility with minimum stretch ensuring the slats overlap correctly when in the closed position. Standard ladder spacing between slats is 44mm/~1.73in.
8. INSTALLATION BRACKETS	Brackets are made of steel and color matched to the headrail. The front is hinged to lock the headrail in place. For blinds over 60" wide a center bracket will be provided. Extension and hold down brackets are available at no charge when requested.